Author Index

Ahn, J.	A three-dimensional algorithm using two-dimensional slice data for building multiple parts in layered manufacturing	365–378
Allen, J. P.	Compensation algorithms for the real-time correction of time and spacial errors in a vertical machining centre	221–234
Atkinson, H.	An evaluation model for determining the business process benefits of thixoforming	11–23
Atkinson, J.	Overcut in pulsed electrochemical grinding	259–269
Backhouse, C. J.	Improving product introduction through appropriate organization: the development of the SIMPLOFI positioning tool	339–364
Backhouse, C. J.	The implementation of a control system for a product introduction process	645–656
Bahai, H.	Surface alignment based on the moment of inertia and improved least-squares methods	547–554
Benati, F.	Surface topography in autobody manufacture—the state of the art	811–820
Benhadj, R.	Performance tests characteristic of a pneumatic proximity tactile array sensing device	901–914
Blake, M. D.	Compensation algorithms for the real-time correction of time and spacial errors in a vertical machining centre	221–234
Bohan, M. F. J.	The effect of process parameters on product quality of rotogravure printing	205–219
Bowen, B. A.	User-responsive interface generation for manufacturing systems: a theoretical basis	379-392
Brookes, N.J.	Improving product introduction through appropriate organization: the development of the SIMPLOFI positioning tool	339-364
Brookes, N. J.	The implementation of a control system for a product introduction process	645-656
Brunn, P.	An effective genetic algorithm for job shop scheduling	293–300
Burns, N. D.	Improving product introduction through appropriate organization: the development of the SIMPLOFI positioning tool	339–364
Burns, N. D.	The implementation of a control system for a product introduction process	645–656
Butler, C.	Surface topography in autobody manufacture—the state of the art	811–820
Carpenter, I. D.	Automatic tool selection for milling operations. Part 1: cutting data generation	271–282
Carpenter, I. D.	Automatic tool selection for milling operations. Part 2: tool sorting and variety reduction	283–292
Chang, C.-C.	Application of a neural network for improving the quality of five-axis machining	47–59
Chang, C.-H.	Application of a neural network for improving the quality of five-axis machining	47–59
Chattopadhyay, A. B.	Assessment of machining features for tool condition monitoring in face milling using an artificial neural network	535–546
Chen, S.-L.	Application of a neural network for improving the quality of five-axis machining	47–59
Chen, Y. W.	Flexible forming of sheet metal using a plasma arc	117–125
Cheung, C. F.	Modelling and simulation of surface topography in ultra-precision diamond turning	463–480
Cheung, K. C.	An intelligent sensor for machined parts inspection	723–734
Chun, K. J.	Leakage characteristics of non-contact seal types for high-speed spindles	481–493
Claypole, T. C.	The effect of process parameters on product quality of rotogravure printing	205–219
Corfe, A. G.	The influence of assist gas on the mechanism of material ejection and removal during laser percussion drilling	521–527
Crafoord, R.	Control of chip flow direction in high-pressure water jet-assisted orthogonal tube turning	529–534
Cuesta, E.	Automatic selection of clamping surfaces in the turning process for rotational parts	693–708
Dale, B. G.	An analysis of self-assessment practices using the business excellence model	593–602
Dale, B. G.	Policy deployment: modelling the CRISP process	603–610
Dale, B. G.	Management system standards: the key integration issues	771–780
Dariani, B. M.	Effect of pre-straining and grain size on the limit strains in sheet metal forming	821–827
Dickens, P. M.	Using stereolithography tools for injection moulding: research into tensile tool failure and unexpected benefits of the process	891–899
Dimov, S. S.	The RapidTool process: technical capabilities and applications	107–116
Dunsmore, W.	Semi-controlled experiment plans for improved mechanical engineering designs	95–105
Dutta, R. K.	Assessment of machining features for tool condition monitoring in face milling using an artificial neural network	535–546
ElMaraghy, H. A.	Optimal workpiece orientations for machining of sculptured surfaces	671–681
Esat, I. I.	Surface alignment based on the moment of inertia and improved least-squares methods	547–554
Fadaie Tehrani, A.	Overcut in pulsed electrochemical grinding	259–269

© IMechE 2000

Farrukh, C. J. P.	Development of a structured approach to assessing technology management practice	313–321
Ford, D. G.	The iterative calculation of the Cartesian geometry of general non-Cartesian structures	149–154
Ford, D. G.	Compensation algorithms for the real-time correction of time and spacial errors in a vertical machining centre	221–234
Fox, M. D. T.	Optical sensor for detection of errors in Nd:YAG laser overlap welding of zinc-coated steel	793–798
Freeman, J. M.	The iterative calculation of the Cartesian geometry of general non-Cartesian structures	149–154
Gethin, D. T.	The effect of process parameters on product quality of rotogravure printing	205–219
Gibson, I.	Improving surface quality of selective laser sintered rapid prototype parts using robotic finishing	197–203
Griffiths, B. J.	Surface topography in autobody manufacture—the state of the art	811–820
Gupta, N.	Swept volume of a generic cutter	915–938
Han, D.-C.	Leakage characteristics of non-contact seal types for high-speed spindles	481–493
Hand, D. P.	Optical sensor for detection of errors in Nd:YAG laser overlap welding of zinc-coated steel	793–798
Hayhurst, D. R.	Use of technological constraints as enumeration criteria for the solution of a travelling salesman problem applicable to production machinery	61–77
Hinds, B. K.	Drilling of printed circuit boards: factors limiting the use of smaller drill sizes	35–45
Hodgson, A.	User-responsive interface generation for manufacturing systems: a theoretical basis	379–392
Hopkinson, N.	Using stereolithography tools for injection moulding: research into tensile tool failure and unexpected benefits of the process	891–899
Hu, D.	Three-dimensional finite element modelling of laser surface modification	683–692
Huang, G. Q.	Modelling the customer–supplier interface over the world-wide web to facilitate early supplier involvement in the new product development	759–769
Huang, J.	Grasping analysis for automated assembly based on a combination of gripping models and qualitative reasoning	25-34
Hui, I. K.	Voiding and printing characteristics of solder paste at different degrees of exposure	137–148
Hur, J.	A three-dimensional algorithm using two-dimensional slice data for building multiple parts in layered manufacturing	365–378
Issac, M.	Swept volume of a generic cutter	915–938
Jacquel, D.	Design for manufacturability: a feature-based agent-driven approach	865–879
Jia, Z. X.	The mechanism of material removal in ultrasonic drilling of engineering ceramics	805–810
Jones, J. D. C.	Optical sensor for detection of errors in Nd:YAG laser overlap welding of zinc-coated steel	793–798
Kaminski, J.	Control of chip flow direction in high-pressure water jet-assisted orthogonal tube turning	529–534
Karunakaran, K. P.	Swept volume of a generic cutter	915–938
Kathuria, Y. P.	Metal rapid prototyping via a laser generating/selective sintering process	1–9
Katz, Z.	Grasping analysis for automated assembly based on a combination of gripping models and qualitative reasoning	25–34
Kermode, G. R.	Value analysis—the technique: state of the art and future directions	301–312
Khan, M. A.	Use of technological constraints as enumeration criteria for the solution of a travelling salesman problem applicable to production machinery	61–77
Khan, W. A.	Use of technological constraints as enumeration criteria for the solution of a travelling salesman problem applicable to production machinery	61–77
Kiran, G.	Assessment of machining features for tool condition monitoring in face milling using an artificial neural network	535–546
Kochhar, A. K.	New product introduction practices in the British manufacturing industry	853–863
Kopač, J.	Dynamic stabilization of the turn-milling process by parameter optimization	127–135
Kovacevic, R.	Parameters optimization for the generation of a keyhole weld pool during the start-up segment in variable-polarity plasma arc welding of aluminium alloys	393–400
Kovacevic, R.	Real-time image processing of keyhole puddle in variable polarity plasma arc welding	495–504
Kovacevic, R.	Three-dimensional finite element modelling of laser surface modification	683–692
Krishna Kumar, R.	Finite element simulation of the railway coach shell assembly process	581–592
Labudovic, M.	Three-dimensional finite element modelling of laser surface modification	683–692
Lacan, F.	The RapidTool process: technical capabilities and applications	107–116
Lagerberg, S.	Control of chip flow direction in high-pressure water jet-assisted orthogonal tube turning	529–534
Lawrence, J.	Finite element analysis of temperature distribution using ABAQUS for a laser-based tile grout sealing process	451–461
Lee, H. C.	A three-dimensional algorithm using two-dimensional slice data for building multiple parts in layered manufacturing	365–378

© IMechE 2000

Lee, J. I.	Prediction of process parameters for gas metal arc welding by multiple regression analysis	443–449
Lee, K.	A three-dimensional algorithm using two-dimensional slice data for building multiple parts in layered manufacturing	365–378
Lee, R. G.	Policy deployment: modelling the CRISP process	603–610
Lee, W. B.	Detection of interference elements and release directions in die-cast and injection-moulded components	431–441
Lee, W. B.	Modelling and simulation of surface topography in ultra-precision diamond turning	463–480
Lewis, S. M.	Semi-controlled experiment plans for improved mechanical engineering designs	95–105
Li, L.	Finite element analysis of temperature distribution using ABAQUS for a laser-based tile grout sealing process	451–461
Li, L.	The influence of assist gas on the mechanism of material ejection and removal during laser percussion drilling	521–527
Li, P. J.	Flexible forming of sheet metal using a plasma arc	117–125
Lim, B. H.	The Nexus method for evaluating geometric dimensioning and tolerancing problems with position callout	235–241
Ljungkrona, O.	Control of chip flow direction in high-pressure water jet-assisted orthogonal tube turning	529–534
Loftus, M.	An image-based fast three-dimensional modelling method for virtual manufacturing	709–721
Low, D. K. Y.	The influence of assist gas on the mechanism of material ejection and removal during laser percussion drilling	521–527
Lowe, A.	An evaluation model for determining the business process benefits of thixoforming	11–23
Lu, H. Y.	Detection of interference elements and release directions in die-cast and injection-moulded components	431–441
McCarthy, I.	An evaluation model for determining the business process benefits of thixoforming	11–23
McMahon, C. A.	The influence of quenchant agitation on the heat transfer coefficient and residual stress development in the quenching of steels	555–567
Mak, K. L.	Modelling the customer–supplier interface over the world-wide web to facilitate early supplier involvement in the new product development	759–769
Maksoud, T. M. A.	In-process automatic dressing system for grinding wheels	799–803
Male, A. T.	Flexible forming of sheet metal using a plasma arc	117–125
Maropoulos, P. G.	Automatic tool selection for milling operations. Part 1: cutting data generation	271–282
Maropoulos, P. G.	Automatic tool selection for milling operations. Part 2: tool sorting and variety reduction	283–292
Marrir, F.	Performance tests characteristic of a pneumatic proximity tactile array sensing device	901–914
Mateos, S.	Automatic selection of clamping surfaces in the turning process for rotational parts	693–708
Miller, R.	Fixtureless assembly of sheet metal parts for the aircraft industry	173–182
Monfared, R. P.	User-responsive interface generation for manufacturing systems: a theoretical basis	379–392
Na, B. C.	Leakage characteristics of non-contact seal types for high-speed spindles	481–493
Nee, A. Y. C.	An intelligent fixture with a dynamic clamping scheme	183–196
Ng, F. M.	The design and planning of cable harness assemblies	881–890
Ngoi, B. K. A.	The Nexus method for evaluating geometric dimensioning and tolerancing problems with position callout	235–241
Ong, A. S.	The Nexus method for evaluating geometric dimensioning and tolerancing problems with position callout	235–241
Paul, S.	Assessment of machining features for tool condition monitoring in face milling using an artificial neural network	535–546
Peng, Q.	An image-based fast three-dimensional modelling method for virtual manufacturing	709–721
Peters, C.	Optical sensor for detection of errors in Nd:YAG laser overlap welding of zinc-coated steel	793–798
Phaal, R.	Development of a structured approach to assessing technology management practice	313–321
Pham, D. T.	The RapidTool process: technical capabilities and applications	107–116
Pham, D. T.	Prediction and reduction of build times for the selective laser sintering process	425–430
Pitts, G.	Semi-controlled experiment plans for improved mechanical engineering designs	95–105
Platfoot, R. A.	A flexible data acquisition system to support process identification and characterization	569–579
Please, C. P.	Semi-controlled experiment plans for improved mechanical engineering designs	195–105
Pogačnik, M.	Dynamic stabilization of the turn-milling process by parameter optimization	127–135
Postlethwaite, S. R.	Compensation algorithms for the real-time correction of time and spacial errors in a vertical machining centre	221–234
Probert, D. R.	Development of a structured approach to assessing technology management practice	313–321
Qiao, H.	Combination of strategy investigation and utilization of sensor signals in robotic assembly	657–669

© IMechE 2000

Raju, V.	Fixtureless assembly of sheet metal parts for the aircraft industry	173–182
Ralph, B.	Voiding and printing characteristics of solder paste at different degrees of exposure	137–148
Ramesh Babu, N.	A hybrid approach for selection of optimal process parameters in abrasive water jet cutting	781–791
Rhee, S.	Prediction of process parameters for gas metal arc welding by multiple regression analysis	443–449
Rico, J. C.	Automatic selection of clamping surfaces in the turning process for rotational parts	693–708
Ridgway, K.	An evaluation model for determining the business process benefits of thixoforming	11–23
Ritchie, J. M.	The design and planning of cable harness assemblies	881–890
Ritchie, L.	An analysis of self-assessment practices using the business excellence model	593–602
Roome, L.	Performance tests characteristic of a pneumatic proximity tactile array sensing device	901–914
Sacerdotti, F.	Surface topography in autobody manufacture—the state of the art	811–820
Sadough, A.	Effect of pre-straining and grain size on the limit strains in sheet metal forming	821–827
Salmon, J.	Design for manufacturability: a feature-based agent-driven approach	865–879
Sedighi, M.	The influence of quenchant agitation on the heat transfer coefficient and residual stress development in the quenching of steels	555–567
Senthil kumar, A.	An intelligent fixture with a dynamic clamping scheme	183–196
Senthil Kumaran, M,	Finite element simulation of the railway coach shell assembly process	581–592
Sexton, C. J.	Semi-controlled expertiment plans for improved mechanical engineering designs	95–105
Shahin, T. M. M.	Value analysis—the technique: state of the art and future directions	301–312
Shakeri, M.	Effect of pre-straining and grain size on the limit strains in sheet metal forming	821–827
Shi, D.	Improving surface quality of selective laser sintered rapid prototype parts using robotic finishing	197–203
Simmons, J. E. L.	The design and planning of cable harness assemblies	881–890
Sitarama Chakravarthy, P.	A hybrid approach for selection of optimal process parameters in abrasive water jet cutting	781–791
Sivaloganathan, S.	Value analysis—the technique: state of the art and future directions	301–312
Sriraman, R.	Finite element simulation of the railway coach shell assembly process	581–592
Suárez, C. M.	Automatic selection of clamping surfaces in the turning process for rotational parts	693–708
Sun, J. L.	The mechanism of material removal in ultrasonic drilling of engineering ceramics	805–810
Tam, S. M.	An intelligent sensor for machined parts inspection	723–734
Tao, Z. J.	An intelligent fixture with a dynamic clamping scheme	183–196
Treanor, M.	Drilling of printed circuit boards: factors limiting the use of smaller drill sizes	35–45
Vafaeesefat, A.	Optimal workpiece orientations for machining of sculptured surfaces	671–681
Valiño, G.	Automatic selection of clamping surfaces in the turning process for rotational parts	693–708
van Voorthuysen, E. J.	A flexible data acquisition system to support process identification and characterization	569–579
Vivekananda Shanmuganathan, P.	Swept volume of a generic cutter	915–938
Walczyk, D. F.	Fixtureless assembly of sheet metal parts for the aircraft industry	173–182
Wang, H.	Real-time image processing of keyhole puddle in variable polarity plasma arc welding	495–504
Wang, Q. I.	Parameters optimization for the generation of a keyhole weld pool during the start-up segment in variable-polarity plasma arc welding of aluminium alloys	393–400
Wang, Q.	Real-time image processing of keyhole puddle in variable polarity plasma arc welding	495–504
Wang, W.	An effective genetic algorithm for job shop scheduling	293–300
Wang, X.	Prediction and reduction of build times for the selective laser sintering process	425–430
West, A. A.	User-responsive interface generation for manufacturing systems: a theoretical basis	379–392
Wilkinson, G.	Management system standards: the key integration issues	771–780
Williams, M. A.	New product introduction practices in the British manufacturing industry	853–863
Wong, L. M. J.	In-process automatic dressing system for grinding wheels	799–803
Wu, C. L.	The mechanism of material removal in ultrasonic drilling of engineering ceramics	805–810

© IMechE 2000

Zhang, B.	Combination of strategy investigation and utilization of sensor signals in robotic assembly	657–669
Zhang, Q. H.	The mechanism of material removal in ultrasonic drilling of engineering ceramics	805–810
Zhang, S. B.	Stability of keyhole in plasma arc welding	401–405
Zhang, Y. M.	Flexible forming of sheet metal using a plasma arc	117–125
Zhang, Y. M.	Stability of keyhole in plasma arc welding	401–405
Zheng, B.	Parameters optimization for the generation of a keyhole weld pool during the start-up segment in variable-polarity plasma arc welding of aluminium alloys	393–400
Zheng, B	Real-time image processing of keyhole puddle in variable polarity plasma arc welding	495–504

Short Communications in Manufacture and Design

Alder, G. M.	A direct analytical solution to the tool design problem in electrochemical machining under steady state conditions	745–750
Antonis, J.	The development of an active computer vision system for reverse engineering	615–618
Armstrong, P. J.	The development of an active computer vision system for reverse engineering	615–618
Arokiam, I. C.	The application of cellular manufacturing: a regional small to medium enterprise perspective	751–754
Backhouse, C. J.	Working the boundaries in the motor industry	941–946
Balasubramanian, S.	Intelligent control for holonic manufacturing systems	953–961
Balon, S. A. P.	Fabrication of microcylindrical parts based on a novel grinding apparatus	245–249
Barnes, C. J.	Evaluation of assembly sequences in an assembly-oriented design environment	89–93
Beng, T. S.	Virtual concurrent product development of plastic injection moulds	165–168
Bennett, R.	Conditions for the successful implementation of finite capacity/MRPII hybrid control systems	847–851
Boughton, N. J.	The application of cellular manufacturing: a regional small to medium enterprise perspective	751–754
Bowyer, A.	Self-assembly of micrometre-scale polymer structures using biochemical recognition	755–758
Britton, G.	Virtual concurrent product development of plastic injection moulds	165–168
Brookes, N. J.	Working the boundaries in the motor industry	941–946
Brujic, D.	Triangulation of unordered data using trimmed NURBS computer aided design models	509–514
Burns, N. D.	Working the boundaries in the motor industry	941–946
Clifton, D.	A direct analytical solution to the tool design problem in electrochemical machining under steady state conditions	745–750
Dibbi, S.	Optimal stock removal in LOM-RP	947–951
Dimov, S. S.	Intelligent product manuals	411–419
Eisenthal, D. C. R.	Self-assembly of micrometre-scale polymer structures using biochemical recognition	755–758
Eisenthal, R.	Self-assembly of micrometre-scale polymer structures using biochemical recognition	755–758
Elliner, G. R.	Via and embedded resistor formation by matrix-assisted pulsed laser deposition	837–839
Gilbert, J. M.	Via and embedded resistor formation by matrix-assisted pulsed laser deposition	837–839
Gyepi-Garbrah, I.	Self-assembly of micrometre-scale polymer structures using biochemical recognition	755–758
Hajee, D. W.	A preliminary study of size reduction of powders in a single-vessel pharmaceutical processor	251–253
Handayani, S.	Triangulation of unordered data using trimmed NURBS computer aided design models	509–514
Harrey, P.	Via and embedded resistor formation by matrix-assisted pulsed laser deposition	837–839
Harrison, D.	Via and embedded resistor formation by matrix-assisted pulsed laser deposition	837–839
Hinds, B. K.	Three-dimensional garment computer aided design—a new approach	619–623
Horrill, M. D.	A preliminary study of size reduction of powders in a single-vessel pharmaceutical processor	251–253
Hubble, J.	Self-assembly of micrometre-scale polymer structures using biochemical recognition	755–758
Jared, G. E. M.	Evaluation of assembly sequences in an assembly-oriented design environment	89–93
Jeffreys, D.	Dimensional control as an integral part of next-generation aircraft development	831–835
Kao, Y.-C.	Collaborative virtual cutting verification and remote robot machining through the Internet	635–644
Kakaraparti, S.	Optimal stock removal in LOM-RP	947–951
Karunakaran, K. P.	Optimal stock removal in LOM-RP	947–951
Kay, G. R.	A preliminary study of size reduction of powders in a single-vessel pharmaceutical processor	251–253
Key, P. H.	Via and embedded resistor formation by matrix-assisted pulsed laser deposition	837–839
Lagarrigue, P.	Improved positioning of a conical mill for machining ruled surfaces: application to turbine blades	625–634

© IMechE 2000

Lam, S. M.	Automatic recognition of machining features from computer aided design part models	515–520
Lamming, R. C.	A preliminary study of size reduction of powders in a single-vessel pharmaceutical processor	251–253
Leaney, P. G.	Dimensional control as an integral part of next-generation aircraft development	831–835
Lee, J.-N.	Collaborative virtual cutting verification and remote robot machining through the Internet	635–644
Lee, R.-S.	Collaborative virtual cutting verification and remote robot machining through the Internet	635–644
Lettice, F. E.	Working the boundaries in the motor industry	941–946
Li, M.	A preliminary study of size reduction of powders in a single-vessel pharmaceutical processor	251–253
Li, W. D.	Recognition of overlapping machining features based on hybrid artificial intelligent techniques	739–744
Li, X.	Wavelet analysis of acoustic emission signals in boring	421–424
Li, X. P.	A discrete model method for three-dimensional parting line search	841–846
Li, Z. Z.	A discrete model method for three-dimensional parting line search	841–846
Lim, T. C.	Effect of textile geometry on axisymmetric stretch forming of knitted fabric composites	333–337
Lin, G. C. I.	Collaborative virtual cutting verification and remote robot machining through the Internet	635–644
Lu, T.-F.	Collaborative virtual cutting verification and remote robot machining through the Internet	635–644
McCartney, J.	Three-dimensional garment computer aided design—a new approach	619–623
MacGregor, S. A.	A preliminary study of size reduction of powders in a single-vessel pharmaceutical processor	251–253
Mei, H.	Adding expert support to assembly-oriented computer aided design tools	81–88
Mill, F.	A direct analytical solution to the tool design problem in electrochemical machining under steady state conditions	745–750
Monies, F.	Improved positioning of a conical mill for machining ruled surfaces: application to turbine blades	625–634
Nee, A. Y. C.	Recognition of overlapping machining features based on hybrid artificial intelligent techniques	739–744
Nee, A. Y. C.	A discrete model method for three-dimensional parting line search	841–846
Newnes, L. B.	A preliminary study of size reduction of powders in a single-vessel pharmaceutical processor	251–253
Norrie, D. H.	Intelligent control for holonic manufacturing systems	953–961
Ong, S. K.	Recognition of overlapping machining features based on hybrid artificial intelligent techniques	739–744
Onwubolu, G.C.	Manufacturing cell scheduling using genetic algorithms	159–164
Onwubolu, G.C.	Cellular manufacturing systems design using Tabu search	169–172
Page, T.	A preliminary study of size reduction of powders in a single-vessel pharmaceutical processor	251–253
Peat, B. J.	Intelligent product manuals	411–419
Petty, D. J.	Conditions for the successful implementation of finite capacity/MRPII hybrid control systems	847–851
Pham, D. T.	Neural network classification of defects in veneer boards	255–258
Pham, D. T.	Intelligent product manuals	411–419
Raju, D. S.	Optimial stock removal in LOM-RP	947–951
Ramakrishna, S.	Effect of textile geometry on axisymmetric stretch forming of knitted fabric composites	333–337
Ramsey, B.	Via and embedded resistor formation by matrix-assisted pulsed laser deposition	837–839
Redonnet, J.-M.	Improved positioning of a conical mill for machining ruled surfaces: application to turbine blades	625–634
Ristic, M.	Triangulation of unordered data using trimmed NURBS computer aided design models	509–514
Robinson, P. A.	Adding expert support to assembly-oriented computer aided design tools	81–88
Rubio, W.	Improved positioning of a conical mill for machining ruled surfaces: application to turbine blades	625–634
Sagiroglu, S.	Neural network classification of defects in veneer boards	255–258
Shang, H. M.	Effect of textile geometry on axisymmetric stretch forming of knitted fabric composites	333–337
Smart, P. K.	Working the boundaries in the motor industry	941–946
Songore, V.	Cellular manufacturing systems design using Tabu search	169–172
Staniforth, J. N.	A preliminary study of size reduction of powders in a single-vessel pharmaceutical processor	251–253

© IMechE 2000

Stirling, M. D.	Conditions for the successful implementation of finite capacity/MRPII hybrid control systems	847–851
Sun, R.-L.	A follow-up control system for flying cut	327–331
Swift, K. G.	Evaluation of assembly sequences in an assembly-oriented design environment	89–93
Tobyn, M. J.	A preliminary study of size reduction of powders in a single-vessel pharmaceutical processor	251–253
Travis, L. C.	Conditions for the successful implementation of finite capacity/MRPII hybrid control systems	847–851
Tsai, J.-P.	Collaborative virtual cutting verification and remote robot machining through the Internet	635–644
Vivekananda Shanmuganathan, P.	Optimal stock removal in LOM-RP	947–951
Wang, Y.	Virtual concurrent product development of plastic injection moulds	165–168
Whish, W. J. D.	Self-assembly of micrometre-scale polymer structures using biochemical recognition	755–758
Wong, D.	A preliminary study of size reduction of powders in a single-vessel pharmaceutical processor	251–253
Wong, T. N.	Automatic recognition of machining features from computer aided design part models	515–520
Wu, J.	Wavelet analysis of acoustic emission signals in boring	421–424
Yeo, S. H.	Fabrication of microcylindrical parts based on a novel grinding apparatus	245–249
Zhang, X.	Intelligent control for holonic manufacturing systems	953–961

© IMechE 2000